



产品认证证书

证书编号: CQC15002123227

申请人名称及地址

Everel Group S.p.A.
Via Cavour 9 37067 VALEGGIO SUL MINCIO (VR), 意大利

制造商名称及地址

Everel Group S.p.A.
Via Cavour 9 37067 VALEGGIO SUL MINCIO (VR), 意大利

生产企业名称及地址

EVEREL ROMANIA SRL (V021291)
Loc.Lipova Str.TIMISORII,Nr.109 315400 Arad, 罗马尼亚

产品名称和系列、规格、型号 器具开关

A1, A2, A4 (具体型号规格详见附件) IP40 耐热3级 PTI250 锡焊端子 插片端子 污染等级2

产品标准和技术要求

GB15092.1-2010

认证模式

产品型式试验+初次工厂检查+获证后监督

上述产品符合CQC11-462124-2009认证规则的要求, 特发此证。

发证日期: 2015年05月12日

证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

主任: _____



中国质量认证中心

中国·北京·南四环西路188号9区 100070

<http://www.cqc.com.cn>

C 0070375



PRODUCT CERTIFICATE

No.: CQC15002123227

NAME AND ADDRESS OF THE APPLICANT

Everel Group S.p.A.
Via Cavour 9 37067 VALEGGIO SUL MINCIO (VR), Italy

NAME AND ADDRESS OF THE MANUFACTURER

Everel Group S.p.A.
Via Cavour 9 37067 VALEGGIO SUL MINCIO (VR), Italy

NAME AND ADDRESS OF THE FACTORY

EVEREL ROMANIA SRL (V021291)
Loc.Lipova Str.TIMISORII,Nr.109 315400 Arad,ROMANIA

NAME, MODEL AND SPECIFICATION

Switch for Appliances
A1, A2, A4 (具体型号规格详见附件) IP40 耐热3级 PTI250 锡焊端子 插片端子 污染等级2

THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB15092.1-2010

CERTIFICATION MODEL

Type Testing of Product + Initial Factory Inspection + Follow up Factory Inspection

This is to certify that the above mentioned products have met the requirements of certification rules
CQC11-462124-2009.

Date of issue: May.12,2015

Validity of this certificate is subject to positive result of the regular follow up inspection by issuing
certification body until the expiry date.

President:

Wang Kejiao



CHINA QUALITY CERTIFICATION CENTRE

Section 9, No.188, Nansihuan Xilu, Beijing 100070 P.R.China
<http://www.cqc.com.cn>

C 0070375



产品认证证书

附录:

证书编号: CQC15002123227

第 1 页 共 1 页

纸号: 70375

具体规格如下:

	A1		A2		A4	
Rated voltage AC	Rated current	Operating cycles	Rated current	Operating cycles	Rated current	Operating cycles
250 V	3 (1) A	10E3	3 (1) A	10E3	3 (1) A	10E3
	6 (2) A	10E3	6 (2) A	10E3	6 (2) A	10E3
	10 (2) A	10E3	10 (2) A	10E3	10 (2) A	10E3
	10 (4) A	10E3	10 (4) A	10E3	10 (4) A	10E3
	13 (4) A	10E3	13 (4) A	10E3	13 (4) A	10E3
	6 (6) A	10E3/50E3	-	-	-	-
	1 (0,05) A	50E3	1 (0,05) A	50E3	1 (0,05) A	50E3
	3 (1) A	50E3	3 (1) A	50E3	3 (1) A	50E3
	6 (1) A	50E3	6 (1) A	50E3	6 (1) A	50E3
	6 (4) A	50E3	6 (4) A	50E3	6 (4) A	50E3
400 V	-	-	-	-	6 A	10E3
Type and connection of switches	Rocker switch continuous contact code: 1.2(1.2 NO or 1.2 NC) momentary contact code: 2.3, 3.3 code 1.2 optional with signal indicator		Rocker switch continuous contact code: 1.2, 2 x 1.2 NO, NC momentary contact code: 2.3, 3.3 code 1.2 and 2 x 1.2 optional with signal indicator		Rocker switch continuous contact code: 1.2, 1.3, 2.3, 2 x 2.3, 2 x 3.3 momentary contact code: 1.2, 1.3, 2.3, 2 x 2.3, 2 x 3.3 code 1.3 optional with signal indicator	

General:

Ambient air temperature	direct actuating 125 / 55 °C	Circuit disconnection	Micro disconnection Only 6 (4) A, 13 (4) A
	indirect actuating 125 °C		Full disconnection The other types

主任: _____

注: 此附录与证书同时使用时有效。

中国质量认证中心

中国·北京·南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>

